## Waterproofing

# **AquaArm Right coat-TC**

(Formerly known as MYK RIGHT COAT)
Single Component Water-based
Acrylic Waterproofing coating for
Interior & Exterior



### **Product Description**

It is single component water based acrylic waterproof coating. It can be applied to most structural surfaces to make them waterproof. The coating is UV stable and highly reflective with high flexibility.

#### **Uses**

- It is used for waterproofing of all types of RCC surfaces such as roofs chajjas, Parapet walls and external walls.
- Asbestos cement sheets roofs can also be waterproofed using scrim cloth or Aso Joint Tape at the junctions overlaps and J bolts as reinforcement.
- As a damp proof course applied under the first layer of bricks or blocks in masonry works.

### **Features and Benefits**

- UV Stable hence can be used for external application.
- Seamless application
- · Single component and easily brush applied
- Breathable
- Cures to give a permanently flexible and resilient surface resistant to a wide range of temperatures
- Can be used on wet surfaces and during rainy season
- Mechanical damages to the membrane can easily be repaired by spot application
- No cleaning solvents are 'required and can be washed off with water when it is still wet.

## **Application Method**

### Mixing & Application:

Surface is thoroughly prepared and devoid any of impurities. Then Primer the surface before doing the final-application .

For Primer -Dilute one part by volume of Terracota with one part of clean water and apply with a brush evenly on the surface.

For Coating- Two Coats are recommended. When the primer coat is touch dry apply the first coat. The Second coat to be perpendicular to the first coat, which ensures uniform masking & even application.



Ver/1/Jun 2018 1 of 2

### WATERPROOFING

# **AquaArm Right coat-TC**

(Formerly known as MYK RIGHT COAT)
Single Component Water-based
Acrylic Waterproofing coating for
Interior & Exterior



## **Packaging**

3 & 13 Kg Pack

### Storage and Shelf Life

Store in cool dry place

24 months from date of manufacturing.

### Consumption

1 kg will cover 2 Sqm @ 200 microns DFT

### **Health & Safety**

Use of hand gloves is necessary while mixing the Product In case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

### **Product Categories Available**



## **Legal Note**

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. the user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. the proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.



8-2-703/A, 3rd Floor, Leela Gopal Towers, Road No. 12, Banjara Hills, Hyderabad -500 034

Ver/1/Jun 2018 2 of 2