

### ArmGrout ADD

(Formerly known as MYK GROUT ADD)

Expansive Grout Additive



## TECHNICAL DATA SHEET

### Product Description

ArmGrout ADD is a single component powder Grout additive which is added to cement to produce a free-flow non-shrink expansive grout additive. It is generally used for injection pressure grouting wherever void filling is required and weak concrete structures, honey combed areas etc.

### Uses

- Weak concrete structure
- For Waterproofing by filling pores & cavities
- Honey combed area, voids etc.

### Features and Benefits

- Free flow
- Chloride free
- Excellent adhesion
- Higher fluidity
- Gaseous expansion
- Compensates plastic shrinkage in cement

### Application Method

#### Mixing of ArmGrout ADD:

Add 250 grams pack of ArmGrout ADD into the cement (W/C ratio - 0.45) and mixed with a mechanical mean until a homogeneous mass is obtained.

#### Application of ArmGrout ADD:

Drill holes with electric drilling machines along the honey Combed area and wall floor joints and fix PVC nozzles. Pressure grout should be carried by using hand operated grouting machine through the nozzles starting from one nozzle and stopping the operations when the grout starts coming out from adjacent nozzle, this is done similarly in all the nozzles.

**Packing:** 250 grams pack



### ArmGrout ADD

(Formerly known as MYK GROUT ADD)

Expansive Grout Additive



## TECHNICAL DATA SHEET

### Storage and Shelf Life

Store in cool dry place

Shelf Life: 24 months from date of manufacturing

### Health & Safety

Use of hand gloves is necessary while mixing the product. In case of contact with skin or eyes, use plenty of water to wash and obtain medical help immediately.

### Consumption

250 Grams per bag of cement

### Product Categories Available



### Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.