

ArmGrout HF

(Formerly known as MYK Anchor HF 66)

Polyester Resin Anchor Grout



TECHNICAL DATA SHEET

Product Description

ArmGrout HF is a Polyester based two components, resin system made for to give excellent anchorage with good corrosion resistance.

Uses

- Rock bolting (in tunnels etc)
- Fixing of foundation bolts
- Fixing of reinforcement.

Features and Benefits

- Rapid Strength
- Corrosion resistant
- Even can be applied under water
- Good consistency
- Vibration resistant.

Application Method

Mixing of ArmGrout HF :

The two parts of ArmGrout HF resin and modified filler should be mixed thoroughly with mechanical means until a homogeneous mix is obtained.

Application of ArmGrout HF:

The mixed material should be poured gradually into the clean hole and the bolt or reinforced rod is pressed into such a way that it touches the bottom of the hole and the resin grout fills the annular space. Slightly move the bolt or reinforced rod once or twice so that even spreading of the anchor grout in the annual space.



ArmGrout HF

(Formerly known as MYK Anchor HF 66)

Polyester Resin Anchor Grout

Storage and Shelf Life

Store in cool dry place

Shelf Life: 6 months from date of manufacturing

Packaging

1 Kg pack

Consumption

Depends on hole & bars diameter



TECHNICAL DATA SHEET

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. the user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. the proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.