

ReArm Super Bond

(Formerly known as MYK Bond EBA)

EpoxyResin Based Concrete Bonding Agent



TECHNICAL DATA SHEET

Product Description

- ReArm Super Bond is a solvent free epoxy resin bonding agent, which is supplied as a two pack component in reweighed quantities for ready to mix and use condition.

Uses

- For all areas where bonding is required for old to new concrete
- It is ideal for the extensions and structural repairs in structural concrete buildings, bridges, roads, loading bays etc.
- Used for vertical and horizontal surface where mortar and concrete can be supported by form work for jacketing

Features and Benefits

- High Bond Strength for old to new concrete
- Can be used for critical areas, on Damp Surfaces.
- Can be used for horizontal & vertical surfaces
- Extended pot life for better working time

Application Method

Mixing & Application:

Stir the Hardener and Resin individually with drill mixer of proper size. Then add the entire content of the hardener into Resin container stir the two components thoroughly using a low speed mixer (300-500rpm) for about 2 to 3 Minutes until a uniform color of the mixture is obtained. The mixed ReArm Super Bond should be applied by brush properly and evenly over the well prepared surface. The new concrete has to be placed within 6 to 8 Hrs depending on the temperature.



ReArm Super Bond

(Formerly known as MYK Bond EBA)

Epoxy Resin Based Concrete Bonding Agent



TECHNICAL DATA SHEET

Consumption

1 kg will cover an area of 4 to 5 Sq Mtrs
(Depends on Surface)

Packaging

ReArm Super Bond is supplied in 1Kg, 3 Kg Packs.

Storage & Shelf Life

Store in cool dry place

12 months from date of manufacturing.

Health & Safety

Use of hand gloves is necessary while mixing the product. In case of contact with skin or eyes, use plenty of water to wash and obtain medical help immediately.

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.